


COHYST

2010

JUNE 2017
INTEGRATED MODEL
DOCUMENTATION REPORT



**COHYST 2010—A Total Water Budget Approach to Integrated
Water Management in the Platte River Nebraska**

2017 Documentation of Revised Integrated Model



Sponsors:

Central Nebraska Public Power and Irrigation District

Central Platte Natural Resources District

Nebraska Public Power District

Tri-Basin Natural Resources District

Twin Platte Natural Resources District

Acknowledgements

The 2017 documentation report was prepared primarily by the following.

- Marc Groff and Isaac Mortenson of The Flatwater Group, Inc.
- John Engel, Abby Nelson, Rusty Jones, and Matt McConville of HDR Engineering, Inc.
- Lee Wilson and Roger Miller of Lee Wilson and Associates, Inc.
- Duane Woodward of the Central Platte Natural Resources District.
- Hayden Strickland of Ecological Resource Consultants, Inc. on behalf of CNPPID.

Brandi Flyr of CPNRD, Michael Krondak of NPPD and Landon Shaw formerly with TPNRD all contributed directly to the report.

The entire modeling effort involved substantial interaction with the project sponsors and their technical representatives, both employees and consultants. The following identifies individuals beyond those authors listed above who provided information to and/or reviewed the report.

- CNPPID: Don Kraus, Mike Drain, and Cory Steinke
- NPPD: Brian Barels, Jeff Shafer, and Michael Krondak
- TBNRD: John Thorburn and Nolan Little
- TPNRD: Kent Miller
- Platte River Recovery Implementation Program: Jerry Kenney, Scott Griebeling, and Bill Hahn of Hahn Water Resources.

We especially wish to remember the contributions of the late Jerry Kenney, who was a strong motivator in ensuring the focus of the modeling effort on the most critical water management and environmental issues.

TABLE OF CONTENTS

ES	Executive Summary	ES-1
ES.1	Overview	ES-1
ES.2	Organization of Report	ES-3
ES.3	Results	ES-5
ES.4	Path Forward	ES-6
	Abbreviations and Acronyms	A-1
	Glossary	G-1
1	Introduction	
1.1	Overview of COHYST 2010	1-1
1.2	Participants in COHYST 2010	1-3
1.3	Report Outline	1-3
2	Project Setting	
2.1	Physical Environment	2-1
2.2	Human Environment	2-16
2.3	Institutional Framework	2-26
3	Overview of Models	
3.1	Conceptual Model	3-1
3.2	Model Dimensions	3-3
3.3	Observed Water Balance	3-5
3.4	Technical Approach	3-7
3.5	Model Integration	3-11
3.6	Modeling Process	3-12
3.7	Summary	3-15
4	Datasets	
4.1	Datasets Used by All Models	4-1
4.1.1	Climate	4-1
4.1.2	Elevations and Drainage Network	4-1
4.2	Land Use	4-2
4.2.1	Introduction	4-2
4.2.1.1	Objectives of the Land Use Dataset	4-2
4.2.1.2	Spatial Coverage	4-3
4.2.1.3	Time Coverage	4-3
4.2.2	Method for Development of New Land Use Dataset in Platte River Basin	4-5
4.2.2.1	Irrigable Lands Dataset	4-5
4.2.2.2	Dryland Dataset	4-7
4.2.2.3	Comingled Irrigated Lands Dataset	4-9
4.2.2.4	Annual Dataset Creation and Cell Partitioning	4-9

4.2.2.5	County Scale Adjustments	4-13
4.2.3	Method for Development of New Land Use Dataset Outside Platte River Basin	4-17
4.2.3.1	Census of Agriculture Data	4-18
4.2.3.2	1950 through 1997 Land Use Data	4-18
4.2.3.3	1998 through 2005 land Use Data	4-20
4.2.3.4	Summary of 1950 through 2005 Land Use Data	4-20
4.2.4	Comparison to an Actual Farm	4-26
4.2.5	Method of Development of Land Use Dataset for 2006 thru 2010	4-27
4.3	Watershed Model	4-28
4.3.1	Soils	4-28
4.3.2	Municipal, Domestic, and Industrial Water Use	4-29
4.3.3	QA/QC of Irrigation Water Use	4-31
4.4	Surface Water Model	4-34
4.4.1	Data Compilations	4-34
4.4.2	Created Data Sets	4-36
4.4.2.1	Seepage Datasets	4-36
4.4.2.2	Sutherland Gage	4-37
4.4.2.3	Historic Reach Gains/Losses	4-37
4.4.2.4	System Water Budgets	4-37
4.5	Groundwater Model	4-38
4.5.1	Hydrostratigraphy Dataset	4-38
4.5.2	Initial Heads Data Set	4-39
4.5.3	Initial Estimate of Hydraulic Conductivity	4-42
4.5.4	Initial Estimates of Specific Yield	4-48
5	Watershed Model	
5.1	Model Components	5-1
5.1.1	Climate Model	5-2
5.1.2	Soil Water Balance Model	5-2
5.1.3	Spatial and Temporal Distribution	5-5
5.1.4	Regional Soil Water Balance Model	5-5
5.2	Key Model Inputs	5-5
5.3	Model Construction	5-24
5.4	Model Results	5-24
5.4.1	Global Water Balance	5-25
5.4.2	Groundwater Pumping	5-29
5.4.3	Recharge	5-35
5.4.4	Net Recharge	5-36

6	Surface Water Model	
6.1	Model Purpose	6-1
6.2	STELLA Model Description	6-1
6.3	STELLA Model Components	6-2
6.3.1	Reservoirs	6-4
6.3.2	Stream Gages	6-4
6.3.3	Diversions and Returns	6-5
6.3.4	Hydropower Facilities	6-5
6.3.5	Water Priority System	6-6
6.4	STELLA Model Software	6-6
6.5	Water Budget Elements	6-11
6.5.1	Precipitation/Evaporation	6-11
6.5.2	Reach Gain/Loss	6-11
6.5.3	Seepage	6-12
6.5.4	Crop Deliveries	6-13
6.5.5	Canal Returns	6-13
6.6	Model Parameters and Inputs	6-13
6.6.1	Simulation Period and Computational Time Step	6-13
6.6.2	Initial and Boundary Conditions	6-13
6.6.3	Travel Time	6-14
6.6.4	Anecdotal Reach Gains	6-15
6.7	System Operational Rules	6-16
6.7.1	Lake McConaughy	6-17
6.7.1.1	Operational Modes	6-18
6.7.1.2	FERC Operating Limits and Minimum Releases	6-19
6.7.2	Individual Irrigation Canals	6-21
6.7.2.1	Historical Diversion Patterns	6-21
6.7.2.2	Diversion Seasons	6-22
6.7.2.3	Predicted and Calculated Canal Returns	6-23
6.7.3	Sutherland System	6-24
6.7.3.1	Korty Diversion	6-24
6.7.3.2	Keystone Diversion	6-25
6.7.3.3	Sutherland Reservoir	6-25
6.7.3.4	Lake Maloney	6-26
6.7.4	Tri-County System	6-26
6.7.4.1	Tri-County Diversion	6-26
6.7.4.2	Jeffery Lake	6-27
6.7.4.3	Jeffrey Return	6-27
6.7.4.4	Johnson Lake	6-27
6.7.4.5	E-65 Diversion	6-28
6.7.4.6	Elwood Reservoir and E-65 below Elwood Reservoir	6-28
6.7.4.7	E-65 below Elwood Reservoir/E-67/Phelps Canal	6-29
6.7.4.8	J-2 Return	6-29
6.7.5	Kearney Canal	6-29

6.7.6	Water Priority System	6-30
6.8	Model Calibration	6-31
6.8.1	Calibration Process	6-31
6.8.2	Calibration Results	6-32
6.8.2.1	Stream Gages	6-32
6.8.2.2	Canal Diversions	6-36
6.8.2.3	Reservoirs	6-43
6.8.2.4	Reach-Scale Water Budgets	6-47
6.8.2.5	North Platte Focus Study	6-49
6.8.2.6	Water Priority System	6-50
6.8.2.7	PRRIP Effort	6-50
6.9	Summary	6-51
7	Groundwater Model	
7.1	2013 Adjustments to Address Specific Issues	7-1
7.1.1	Evapotranspiration	7-1
7.1.2	Seepage from Lake McConaughy	7-4
7.1.3	Sutherland Water Levels	7-5
7.2	Model Changes made during Recalibration	7-5
7.3	Conversion to MODFLOW 2005	7-11
7.3.1	Code Conversion	7-11
7.3.2	Stream Boundary Conversion	7-12
7.3.3	Channel Width Adjustments	7-14
7.4	Calibration Method	7-19
7.5	Calibration Results	7-29
7.6	Extension to 2010	7-44
7.7	Gosper-Phelps Focused Study	7-46
8	Integrated Model	
8.1	Integration of Models	8-1
8.1.1	Baseflow and Runoff Exchange	8-3
8.1.2	Recharge from Canal and Reservoirs	8-4
8.1.3	Calculated Irrigation Delivery	8-5
8.1.4	Calibration	8-6
8.2	Integrated Model Results	8-6
8.2.1	Platte River Gages	8-6
8.2.2	Secondary Integrated Calibration Targets	8-11
8.2.3	Reach Gain/Loss	8-11
8.2.4	Flow Duration Curves	8-16
8.3	Comparison of Integrated Results to Phase I Water Budget	8-19
8.3.1	Mean Annual Water Budget Summary	8-19
8.3.2	Annual Water Budget Summary	8-21
8.3.3	Cumulative Water Budget Comparisons	8-26
8.4	Integrated Model Graphical User Interface (GUI)	8-29
8.4.3	GUI Verification	8-30

9	Model Evaluation	
9.1	Model Objectives	9-1
9.2	Model Assumptions and Limitations	9-3
9.2.1	Assumptions and Uncertainties	9-4
9.2.2	Limitations	9-14
9.3	Peer Review	9-15
10	Applications of the COHYST 2010 Models	
10.1	Functionality	10-1
10.2	Suitable Applications of the COHYST 2010 Model	10-1
10.2.1	Conjunctive Water Management Evaluations	10-2
10.2.2	Platte Basin Over-Appropriated Area Evaluations	10-2
10.2.3	Platte River Recovery Implementation Program Evaluations	10-3
10.3	Examples of Some Unsuitable Model Applications	10-6
10.4	Priorities for Model Modifications and Improvements	10-6
10.5	Conclusion	10-7
11	References	
12	Linked Documents and Files	

List of Tables

Table 2.1-1.	Topographic Regions.	2-6
Table 2.2-1.	Census of Agriculture Data Summary for 2007.	2-19
Table 2.2-2.	Natural Flow Water Rights Below Lake McConaughy.	2-22
Table 2.2-3.	Platte River Hydro Power Plant Capacities.	2-26
Table 2.3-1.	Key Provisions of LB 962, LB 483, and LB 54 that are Part of Current Statutes.	2-28
Table 2.3-2.	Average Stream depletion by Natural Resources District in the Platte River Basin.	2-30
Table 2.3-3.	Platte River Program USFWS Target Flows by Hydrologic Conditions.	2-32
Table 2.3-4.	Platte River Program Hydrologic Conditions for the Model Development Time Period.	2-33
Table 3.1-1.	Components of the Platte River Hydrologic Cycle.	3-2
Table 3.3-1.	Observation Based Water Balance to Represent the Entire Hydrologic Cycle in the COHYST 2010 Study Area for the Entire Period 1985-2005. AF=average acre-feet/year.	3-6
Table 3.5-1.	Difference between Historic and Integrated Models.	3-13
Table 5.1.	NWS Weather Stations used in the COHYST Model.	5-9

Table 5.2.	Surface Water Irrigation Districts.	5-15
Table 5.3.	COHYST Runoff Zones.	5-17
Table 5.4.	Long Term Average Water Balance for the COHYST Model.	5-25
Table 5.5.	Long Term Average Annual Applied Irrigation.	5-25
Table 5.6.	Annual Field Water Balance (AF).	5-26
Table 5.7.	Annual Runoff Water Balance (AF).	5-28
Table 6.6-1.	Lake McConaughy Tributary Inflows below Lewellen.	6-14
Table 6.6-2.	Travel Time Estimates.	6-15
Table 6.6-3.	Anecdotal Reach Gain Estimates.	6-16
Table 6.7-1.	Lake McConaughy FERC Operating Limits.	6-20
Table 6.8-1.	Stream Gage Cumulative Volume (1990-2005) Calibration Results.	6-33
Table 7.5-1.	Calibrated Hydraulic Conductivity.	7-35
Table 7.7-1.	Model Errors end 2005 in the Final Integrated Run and in the Gosper-Phelps Study.	7-47
Table 8.1-1.	Integrated Modeling Sequence.	8-2
Table 8.2-1.	Stream gage Cumulative Volume Calculated by Integrated Model Results, for Platte River Gages, 1990-2005.	8-7
Table 8.3-1.	Mean Annual Modeled Water Budget and Balance for Entire Hydrologic Cycle in the COHYST 2010 Study Area for the Entire Period 1985-2005.	8-20

List of Figures

Figure 1.1-1.	COHYST 2010 Study Area.	1-1
Figure 2.1-1.	Platte River Drainage Basins (green shading)	2-2
Figure 2.1-2.	COHYST model boundary, including major river basins.	2-3
Figure 2.1-3.	Study Area Map Showing Topographic Regions (See also Table 2.1-1)	2-5
Figure 2.1-4.	Isohyet Map of Annual Precipitation in COHYST Study Area.	2-7
Figure 2.1-5.	Annual Precipitation at Grand Island, NE, Showing Variations Between Wet and Dry Years.	2-8
Figure 2.1-6.	Grand Island Monthly Precipitation for an "Average" Year, a Year with a Wet July-August (1903) and One with a Dry July-August (2012)	2-9
Figure 2.1-7.	Study Area Map of Soil Type Showing Water Holding Capacity.	2-11
Figure 2.1-8.	Study Area Map Showing the Location of Where Quaternary and Ogallala Formations Used as Groundwater Supply.	2-12

Figure 2.1-9a. Hydrogeology Cross Sections for the Eastern Half of the COHYST 2010 Model Area.	2-13
Figure 2.1-9b. Hydrogeology Cross Sections for the Western Half of the COHYST 2010 Model Area.	2-14
Figure 2.1-10. Study Area Map Showing the Saturated Thickness of the Aquifer	2-15
Figure 2.2-1. Study Area Map of Cities and Highways.	2-17
Figure 2.2-2. Study Area Map Showing Natural Resources Districts.	2-18
Figure 2.2-3. USDA Census of Agriculture Cropland Distribution.	2-20
Figure 2.2-4. Map of COHYST Area Canal Systems.	2-23
Figure 2.2-5. Study Area Irrigation Wells Developed Each Year.	2-24
Figure 2.3-1. Platte River Basin Map of Hydrologically Connected Groundwater Area that is considered Over-appropriated.	2-29
Figure 3.1-1. Illustration of Hydrologic Cycle in which Irrigation is important.	3-2
Figure 3.3-1. Annual Values of Phase I Water Balance for Inflow, Outflow and Change in Storage.	3-7
Figure 3.4-1. Relationships of Components of the Hydrologic Cycle (as listed in Table 3.1-1.).	3-9
Figure 3.4-2. Structure of the COHYST 2012 Models to Reflect the Hydrologic Cycle of Figure 3.4-1.	3-10
Figure 4.2-1. Study Area for COHYST 2010 Land Use Dataset Development.	4-4
Figure 4.2-2. Flowchart of Methods used to create the COHYST 2010 Land Use Dataset	4-6
Figure 4.2-3. Map Showing Input Data Sources Used to Create Potentially Irrigable Lands Dataset.	4-8
Figure 4.2-4. Year 1950 Land Use in COHYST 2010 Acres Redevelopment Area.	4-10
Figure 4.2-5. Year 1985 Land Use in COHYST 2010 Acres Redevelopment Area.	4-11
Figure 4.2-6. Year 2005 Land Use in COHYST 2010 Acres Redevelopment Area.	4-12
Figure 4.2-7. Estimated Irrigated Land Acreage for the Aggregate Study Area.	4-14
Figure 4.2-8. Estimated Dryland Acreage for the Aggregate Study Area.	4-14
Figure 4.2-9. Land Use Acreage Irrigated and Non-Irrigated in Original COHYST Area.	4-21
Figure 4.2-10. Land Use in 1950 for the COHYST Area.	4-22
Figure 4.2-11. Land Use in 1985 for the COHYST Area.	4-23
Figure 4.2-12. Land Use in 2005 for COHYST Area.	4-24
Figure 4.2-13. Changes in Land Use Over Time for Gosper County.	4-25
Figure 4.3-1. Location of Municipal and Industrial Centers.	4-32
Figure 4.3-2. Municipal and Industrial Pumping Over Time.	4-33

Figure 4.4-1.	Major Surface Water Features of the COHYST 2010 Model.	4-35
Figure 4.5-1.	Differences Between Spring, 1979 Head Observations and 1979 Water Table Map Head Elevations.	4-40
Figure 4.5-2.	Differences between October 1984 Head Observations and the 1979 Water Table Map Head Elevations.	4-41
Figure 4.5-3.	Differences between October 1984 Head Observations Constructed Initial Heads.	4-43
Figure 4.5-4.	Ratio of specific Capacity to Aquifer Thickness.	4-45
Figure 4.5-5.	Hydraulic Conductivity Estimated from specific Capacity.	4-46
Figure 4.5-6.	Initial Five Zones of Hydraulic Conductivity.	4-47
Figure 4.5-7.	Ten Hydraulic Conductivity Zones used in the 2013 Calibration of the COHYST2010 Groundwater Model.	4-49
Figure 4.5-8	Initial Specific Yield Zones	4-50
Figure 5.1.	STATSGO2 Soil Coverage within the Model Area.	5-6
Figure 5.2.	CropSim Soil Type Coverage within the Model Area derived from Soil Properties Recorded in the STATSGO2 Soils database.	5-7
Figure 5.3.	CropSim Soil Type Assigned to each 160 Acre Model Grid Cell.	5-8
Figure 5.4.	Location of the Weather Stations and Average Annual Precipitation for the COHYST Model Domain.	5-9
Figure 5.5.	Average Annual Net Irrigation Requirement for Corn within the COHYST Model Domain.	5-12
Figure 5.6.	Development of Irrigated Acres within the COHYST Model Domain.	5-13
Figure 5.7.	Surface Water Irrigation Districts in the COHYST Model Area.	5-14
Figure 5.8.	Surface Water Irrigation Sub-districts within the Central Nebraska Public Power and Irrigation District.	5-15
Figure 5.9.	COHYST Runoff Zones.	5-17
Figure 5.10.	COHYST Coefficient Zones.	5-19
Figure 5.11.	Canal Seepage from the Irrigation District Canals in the Republican River Area.	5-22
Figure 5.12.	Distribution of Municipal and Industrial Pumping within the COHYST Domain.	5-23
Figure 5.13.	Development of Municipal and Industrial Pumping within the COHYST Model Domain.	5-23
Figure 5.13.	Average Volume of Pumping per 160-acre Cell in the COHYST Model Area.	5-30
Figure 5.14.	Development of Groundwater Irrigated Acres in the COHYST Model Domain	5-31

Figure 5.15.	Extent of Groundwater Pumping Per 160-acre Cell in 1985.	5-31
Figure 5.16.	Extent of Groundwater Pumping Per 160-acre Cell in 2010.	5-32
Figure 5.17.	Annual Depth of Pumping Precipitation and Agricultural Pumping in the COHYST Model Domain.	5-33
Figure 5.18.	Annual Volume of Pumping in the COHYST Model Domain.	5-33
Figure 5.19.	Comparison of the Modeled Pumping to Metered Pumping in Perkins County, NE.	5-34
Figure 5.20.	Comparison of Simulated Pumping to Metered Pumping on Irrigated Corn in Merrick County.	5-35
Figure 5.21.	Average Annual Recharge Per 160-acre Cell in the COHYST Model Area.	5-36
Figure 5.22.	COHYST Annual Average Recharge Rates.	5-36
Figure 5.23.	Average Net Recharge Per 160-acre Cell in the COHYST Model Domain.	5-37
Figure 6.3-1.	Platte River STELLA Nodes.	6-3
Figure 6.4-1.	STELLA Schematic for Lake McConaughy Area.	6-8
Figure 6.4-2.	Example of STELLA Knobs and Sliders.	6-9
Figure 6.4-3.	Example of STELLA Operating Rule for Canal Diversion.	6-10
Figure 6.7-1.	Sutherland Reservoir Target Operating vs. Historic Reservoir Elevations.	6-26
Figure 6.7-2.	Elwood Reservoir Target Operating Curve.	6-28
Figure 6.8-1.	Platte River near Duncan Gage Annual Data.	6-34
Figure 6.8-2.	Platte River near Duncan Gage Daily Data.	6-35
Figure 6.8-3.	North Platte Canals Annual Diversion Data.	6-37
Figure 6.8-4.	North Platte Canals Daily Diversion Data.	6-38
Figure 6.8-5.	Gothenburg Canal Annual Diversion Data.	6-39
Figure 6.8-6.	Gothenburg Canal Daily Diversion Data.	6-40
Figure 6.8-7.	Tri-County Supply Canal Annual Diversion Data.	6-41
Figure 6.8-8.	Tri-County Supply Canal Daily Diversion Data.	6-42
Figure 6.8-9.	Lake McConaughy Simulated and Historic Daily Storage.	6-44
Figure 6.8-10.	Sutherland Reservoir Simulated and Historic Daily Storage.	6-45
Figure 6.8-11.	Elwood Reservoir Simulated and Historic Daily Storage.	6-45
Figure 6.8-12.	Reach-scale Annual Water Budget for Sutherland Canal System.	6-48
Figure 6.8-13.	Reach-scale Annual Water Budget for Tri-County Supply Canal System.	6-48

Figure 6.8-14. Gothenburg Canal – Historic and Calculated Natural Flow, Storage Water and Total Diversions.	6-50
Figure 7.1-1. Rate and distribution of 1997 ET calculated by the Documented Model (top) and the Modified Model (bottom) 1997.	7-3
Figure 7.2-1. The SFR Boundary with the Platte River and its Tributaries. Tributary streams are shown in Gray and Drains are shown in Tan. Cells with Diversions are shown in Red.	7-7
Figure 7.3-1. Net Groundwater Balance, Comparing Results from the Conversion to MODFLOW 2005.	7-13
Figure 7.3-2. Net Groundwater Balance, Comparing Results from the Conversion to MODFLOW 2005 with the SFR Module.	7-14
Figure 7.3-3. Net Groundwater Balance, Comparing Results from the Conversion to MODFLOW 2005 with Modified Tributary Widths.	7-15
Figure 7.3-4a. Simulated Discharge of Prairie Creek near Silver Creek.	7-16
Figure 7.3-4b. Simulated Stage of Prairie Creek near Silver Creek.	7-16
Figure 7.3-5a. Simulated Discharge of Buffalo Creek near Overton.	7-17
Figure 7.3-5b. Simulated Stage of Buffalo Creek near Overton.	7-17
Figure 7.3-6a. Simulated Discharge of the Platte River at Odessa.	7-18
Figure 7.3-6b. Simulated Stage of the Platte River at Odessa.	7-18
Figure 7.4-1. Locations of Water Level and Drawdown Data used for Calibration of the COHYST 2010 Groundwater Model. Locations inside the High-Concentration are shown with Gray Shading.	7-21
Figure 7.4-2. Calculated Recharge Lag Times in the COHYST2010 Area, based on an Approximate moisture content in the unsaturated Zone of 20%.	7-26
Figure 7.4-3. Distributions of Zones used to adjust deep Percolation Rates for the Recharge Lag.	7-27
Figure 7.4-4. Hydraulic Conductivity Zones used in the Documented Model Compared to the Simplified Zones in the Current Calibration.	7-30
Figure 7.5-1. Drawdown Difference at the end of the Calibration Period. The Symbols are Relative to a Standard Deviation of 5.49 feet. The Average Difference was 0.345 Feet.	7-31
Figure 7.5-2. Examples of Typical Hydrograph Comparisons.	7-32
Figure 7.5-3. Examples of Excellent Hydrograph Matches.	7-33
Figure 7.5-4. Examples of Bad Hydrograph Comparisons.	7-34
Figure 7.5-5. Hydraulic Conductivity Values resulting from Optimization of the COHYST2010 Groundwater Model.	7-36
Figure 7.5-6. Calibrated Hydraulic Conductivity compared to prior Expectations from specific Capacity Data.	7-37
Figure 7.5-7. Calibrated Hydraulic Conductivity compared to prior Expectations from Lithology-based Estimates done for COHYST.	7-38
Figure 7.5-8. Calibrated Hydraulic Conductivity compared to prior Expectations from CPNRD Aquifer Tests.	7-39
Figure 7.5-9. Specific Yield Zones used for calibrating the COHYST2010 Groundwater	

Model. Values resulting from the Optimization are shown in the Legend.	7-40
Figure 7.5-10. Two Cases in which the Optimization improved the Baseflow Match.	7-42
Figure 7.5-11. Two Cases in which the Optimization did not improve the Baseflow Match.	7-43
Figure 7.6-1. Drawdown Differences at the end of the Calibration Period and Verification Period.	7-45
Figure 7.6-2. Drawdown Differences (calculated-observed) at the end of the Calibration and Verification Periods.	7-46
Figure 7.7-1. Hydraulic Conductivity Zones for Refining Conditions in Gosper and Phelps Counties.	7-48
Figure 7.7-2. Drawdown Differences at the end of 2005 recalibrating the Model to Improve the fit in Gosper and Phelps Counties.	7-49
Figure 8.1-1. Linkage of Individual Models within the Integrated Model.	8-1
Figure 8.1-2. Drainage Basins Used in Watershed Model.	8-4
Figure 8.1-3. Intersection of Surface Water Features with Groundwater Grid Cells.	8-5
Figure 8.2-1. Comparison Calculated and Historic Streamflow and Cumulative Differences, Platte River near Duncan.	8-8
Figure 8.2-2. Annual Total Flow for Calculated, Historical Reach Gain/Loss and Integrated Model Simulation for the Platte River near Duncan.	8-10
Figure 8.2-3. Comparison of Annual and Average Daily Reach Gains/Loss for South Platte River Reach between Julesburg and North Platte.	8-12
Figure 8.2-4. Comparison of Annual and Average Daily Reach Gains/Loss for Platte River Reach between North Platte and Brady.	8-13
Figure 8.2-5. Comparison of Annual and Average Daily Reach Gains/Loss for Platte River Reach between Odessa and Grand Island.	8-14
Figure 8.2-6. Comparison of Annual and Average Daily Reach Gains/Loss for Platte River Reach between Grand Island and Duncan.	8-15
Figure 8.2-7. Comparison of Historic and Calculated Flow Duration for 1990 through 2005.	8-17
Figure 8.2-8. Comparison of Historic and Calculated Flow Duration for Dry Years.	8-18
Figure 8.2-9. Comparison of Historic and Calculated Flow Duration for Normal Years.	8-18
Figure 8.2-10. Comparison of Historic and Calculated Flow Duration for Wet Years.	8-19
Figure 8.3-1. Annual Modeled Water Balance for Inflow, Outflow, and Change in Storage.	8-21
Figure 8.3-2. Annual Observed and Modeled Precipitation.	8-22
Figure 8.3-3. Annual Observed and Modeled Evapotranspiration.	8-23
Figure 8.3-4. Annual Observed and Modeled Platte River Inflow.	8-23
Figure 8.3-5. Annual Observed and Modeled Platte River Flow at Duncan.	8-24
Figure 8.3-6. Annual Observed and Modeled Reservoir Storage Change.	8-24
Figure 8.3-7. Annual Observed and Modeled Groundwater Inflow and Outflow.	8-25
Figure 8.3-8. Annual Observed and Modeled Groundwater Aquifer Storage.	8-25

Figure 8.3-9.	Annual Cumulative Platte River Flow at Duncan for the Observed and Modeled Data.	8-27
Figure 8.3-10.	Annual Cumulative Net Gain for the Observed and Modeled Data.	8-28
Figure 8.3-11.	Annual Cumulative Changes in Groundwater Storage for the Observed and Modeled Data.	8-28

List of Appendices

Appendix 3-A	Phase I Water Budget for Central and Eastern Model Areas
Appendix 3-B	Model Calibration Plan, Updated 2013 version and May 2016 Recalibration Plan
Appendix 4-A	National Weather Service Climate Records
Appendix 4-B	Digital Elevation Model (DEM) Datasets
Appendix 4-C	Drainage Network and Hydrography Datasets
Appendix 4-D	Datasets Used to Create Land Use Information
Appendix 4-E	Method to Spatially Relate Wells to Digitized Fields
Appendix 4-F	Python Programs to Create Annual Land Use
Appendix 4-G	GIS Adjustment Methods for Potential Irrigated Lands
Appendix 4-H	County Estimates of Irrigated and Dryland Acres
Appendix 4-I	Application of Land Use Adjustment Factors at the Cell Scale
Appendix 4-J	Overage Land Use Acres in Model Cells for Specific Years
Appendix 4-K	Redistribution of Overage Land Use Acres in Model Cells
Appendix 4-L	Acquisition of Census of Agriculture Data
Appendix 4-M	Processing of Census of Agriculture Data
Appendix 4-N	County Crop Mix: 1950-2007
Appendix 4-O	Quality Assurance Edge Effects Analysis of County Boundaries and Model Cells
Appendix 4-P	Simulated Historical Land use Distribution: 1950-2005
Appendix 4-Q	Land Use Classification Manual
Appendix 4-R	Processing Municipal, Industrial, and Domestic Withdrawals and Discharge
Appendix 4-S	Municipal, Industrial, and Domestic Water Use Database
Appendix 4-T	List and Source of Surface Water Records
Appendix 4-U	North Platte Focus Study – Sutherland Gage Assessment
Appendix 4-V	Annual System Water Budgets for Tri-County System and the Sutherland System
Appendix 4-W	Initial Heads Datasets for MODFLOW

Appendix 5-A	RSWB Model Construction
Appendix 5-B	Guide to the Watershed Model Programs and Files
Appendix 5-C	Making a Watershed Model Run
Appendix 6-A	Platte River Mapping with STELLA Nodes
Appendix 6-B	STELLA Model Schematic
Appendix 6-C	Canal Seepage Estimates
Appendix 6-D	Lake McConaughy and Tri-County System General Operating Rules
Appendix 6-E	Crop Demand Approach
Appendix 6-F	Sutherland System General Operating Rules
Appendix 6-G	Priority Accounting Summary
Appendix 6-H	STELLA Model Version Summary
Appendix 6-I	Surface Water Model Calibration Results – Main Stem Gages
Appendix 6-J	Surface Water Model Calibration Results – Canal Diversions and Returns
Appendix 6-K	Surface Water Model Calibration Results – Main Stem Gages
Appendix 6-L	North Platte Focus Area Study
Appendix 6-M	Platte River Recovery Implementation Program (PRRIP) Surface Water Model
Appendix 7-A	SFR Module
Appendix 7-B	Groundwater Model River and Drain (RIV & DRN) Packages
Appendix 7-C	Hydrographs at observation locations
Appendix 8-A	Integrated Model Calibration Results – Main Stem Gages
Appendix 8-B	Integrated Model Calibration Results – Canal Diversions and Returns
Appendix 8-C	Integrated Model Calibration Results – Reservoirs
Appendix 8-D	Integrated Model Calibration Results – Reach Scale Water Budgets
Appendix 8-E	Integrated Model Calibration Results – Reach Gain/Loss
Appendix 8-F	Integrated Model Calibration Results – Flow Duration Curves
Appendix 8-G	Graphical User Interface (GUI) User’s Manual
Appendix 9-A	Review of SFR Package
Appendix 9-B	Review Lake McConaughy Operating Rules
Appendix 9-C	E-67 Lining Simulation
Appendix 9-D	Keith-Lincoln Canal Simulation

EXECUTIVE SUMMARY

ES.1 Overview

COHYST is a hydrologic study of the Platte River drainage basin in central Nebraska. COHYST 2010 is a specific project within COHYST that involves developing an integrated computer-based model of basin hydrology to be used to calculate river and aquifer effects of different management scenarios. The goal is to support water management to maintain the region's extensive irrigation economy and protect river habitats used by endangered species.

Phase I of COHYST 2010 involved design of the modeling work, and development of an observation-based water budget for the study area to be used in model evaluation. Phase II of COHYST 2010 had the objective of building the computer models. A potential Phase III may involve applications of and improvements to the modeling tools.

An initial COHYST 2010 model of the Platte River and adjoining basins was published in 2013. Subsequently this model has been successfully applied, especially in the evaluation of alternative scenarios. Significant simplifications of the 2013 model were recognized at the time and many have now been addressed in the model that was calibrated in December 2016 and documented here.

Water budgets are fundamental components of any model of a hydrologic system and provide a quantitative basis to relate water inputs to outputs and to changes in storage. Phase II of COHYST 2010 has built three individual models that address different components of the water budget: watershed model for soils, surface water for lakes, streams and canals, and groundwater model for aquifers. These models are integrated to quantify the total water balance of the system.

Key elements of the water budget that are represented in the models are as follows.

- External sources of water are precipitation, along with streamflow and groundwater from upstream of the study area.

- External sinks (losses) of water are evapotranspiration, along with streamflow and groundwater discharges to downstream of the study area.
- Within the study area, the primary simulations involve calculating water needs on irrigated lands that are not met by precipitation, and computing the diversions of surface and groundwater to satisfy those unmet needs, and the impacts of such diversions.
- The complex system of surface water reservoirs and canals is operated according to historic inflows and known rules to meet crop demands of lands irrigated by surface water. The surface water simulation also operates to represent power generation.
- Known irrigation wells are simulated as pumping in amounts necessary to satisfy crop demands on lands irrigated by groundwater. Pumping for municipal, industrial and domestic uses also is included.
- Water exchanges occur within the system. In particular, some portion of the precipitation and applied water is discharged as runoff to streams or becomes recharge to groundwater; canal seepage becomes recharge; and streams can seep to groundwater or gain flow from groundwater baseflow and from drains.

Common features of the models include the following.

- The three individual models and the integrated model have the same study area which is unchanged from the 2013 model.
- All model inputs and results are organized according to one of two spatial contexts: 160 acre cells, which reflect the landscape scale of typical farming enterprises in the region; or the network of major Platte Basin surface water features (streams, reservoirs, canals).
- The models are calibrated based on matching model results to observations for a 16 year period, 1990-2005. 1985-1989 results are considered where needed to define 1990 starting conditions. An extension of the model for 2006-2010 is used to evaluate model

performance. Time periods used within the models vary, but all results are integrated to a monthly time scale.

ES.2 Organization of Report

The models are documented in 10 sections of this report.

- [Section 1](#) introduces the COHYST 2010 study, describes the structure of the work, and summarizes major changes from the prior 2013 model.
- [Section 2](#) contains descriptive information about the setting of the study, with an emphasis on existing water resources.
- [Section 3](#) describes the construction of the COHYST 2010 models and their relationship to the hydrologic cycle of the basin. The section also describes the model calibration process and presents the Phase 1 water budget, as determined from observed data.
- [Section 4](#) documents data sets which were built during COHYST 2010 to provide external inputs to the model (e.g. climate, soils, land use, stream geometry, layout of canals, municipal pumping, and known aquifer properties) or to provide target observations used to calibrate the model (such as gaged streamflows, reservoir stages and volumes, diversions of surface water, groundwater levels and their changes, estimates of stream reach gains and losses from groundwater).
- [Section 5](#) provides documentation for the watershed model. This model calculates the monthly land-soil water budget for each model cell based on land use, on soil properties, and on daily precipitation data. A UNL crop water use model (CROPSIM) is used to provide a temporal distribution of precipitation and supplied water into evapotranspiration (including consumption by crops), runoff, and deep percolation. For irrigated lands, the model estimates the demand for surface water diversions and groundwater pumping to satisfy crop demands not met by precipitation. Model calibration is judged primarily on whether the water partitioning in the watershed leads to a good performance by the surface water and groundwater models.
- [Section 6](#) provides documentation for the surface water model. Operating rules for reservoirs and canals are used to route inflows from upstream (as augmented by local

runoff and return flows) to meet demands for irrigation, hydropower and power plant cooling. The rules reflect historic operation of major reservoirs and irrigation districts throughout the study area. Model calibration has considered how operations vary between wet and dry periods and how these changed during the period simulated. Model calibration is based on matching gaged streamflows, canal diversions and reservoir conditions.

- [Section 7](#) provides documentation for the groundwater model. The model provides a two-dimensional (one layer) simulation of the response of the regional aquifer to recharge, pumping and discharges to drains and streams. The primary calibration parameter is aquifer hydraulic conductivity, Model performance is judged primarily on the match between simulated and observed hydrographs for a wide array of wells, with a focus on locations near the Platte River. The best calibration recognized the lag effect between recharge at the land surface and water table responses where there is a significant vadose zone thickness.
- [Section 8](#) provides documentation for the final integrated version of the model, denoted as 028b_15_27 based on the model versions for the watershed, surface water and groundwater models respectively. In this, the current integrated model, runoff from the watershed model and discharge from the groundwater model replace the reach gain-loss inputs to the surface water model. The integrated model is the ultimate product of COHYST 2010 Phase II and, in addition to the standalone calibration of the component models, is judged based on the match between simulated and gaged streamflows and on the correspondence of the integrated water budget to the observation-based water budget presented in Section 3.
- [Section 9](#) is the evaluation of model assumptions, limitations and quality, as judged by the modeling team.
- [Section 10](#) provides a brief look forward to anticipated applications and upgrading of the models.

- In addition, [Section 11](#) is a list of references cited in the report, and [Section 12](#) compiles links to data files that provide the model inputs and most recent outputs and to documents that are part of the COHYST files.

Note that citations throughout this report are used to reference several dozen appendices which provide considerable detail about inputs to, the structure of, or outputs from the model.

ES.3 Results

Both the surface water model and groundwater model are considered to be calibrated, and because both calibrations rely on water budget information from the watershed model, that model also is considered to be calibrated. Results from the surface water model are illustrated extensively in Section 6. As shown in that Section, model results are in agreement with the hydrologic patterns over time and are consistent with the overall observed water budget. The agreement between simulated and observed hydrology provides confidence that the modeled surface water operations are a reasonable representation of what occurs in the system. The results also indicate that the watershed model provides reasonable estimates of the amount of water used for surface water irrigation. Most other results from the surface water model are similar in that there is acceptable agreement between model estimates and observed data, with cumulative water balance errors over the 1990-2005 period of a few percent or less at most locations.

Results from the groundwater model are illustrated extensively in Section 7. Comparisons of observed and simulated values indicate that overall model errors are acceptable, with only a few large errors that reflect local conditions that are beyond the ability of the current model to resolve and/or are located outside of the Platte basin and thus not critical to address. Most important, there is no marked spatial bias.

The integrated model water budget reported in Section 8 is in good balance. About 24.5 million acre-feet of annual inflow occurred in the 1985-2005 period, which compares to 24.3 million acre-feet of annual outflow; the total error of less than 0.2 million acre-feet per year is less than 1 percent. Larger errors occur in the prediction of some quantities, as for example gaged streamflow, and have a notable bias in that errors are highest for wet periods. This bias is the

expected result of focusing model calibration on the dry conditions that are most critical to water management for irrigation and environmental purposes. Even so, because the model outputs are summarized on a monthly basis, flows in dry periods can still be sometimes overestimated.

ES.4 Path Forward

The models are considered to be suitable for the intended purpose of Phase II of COHYST 2010, i.e. for many management applications they will provide useful results when run to reflect assumptions about water management, water supply or water use. Results of such runs are considered reliable when interpreted on a regional (county or larger) scale, and on a seasonal or multi-year time scale. The models also provide a platform that can be modified to address issues that were beyond the scope of Phase II, as for example to evaluate impacts from a single well. As with any typical predictive tool, the COHYST model is capable of further improvement but at this time there are no identified major weaknesses for the intended purposes.

Abbreviations and Acronyms

Abbreviation/Acronym	Descriptor
ac	acre
acft, or AF	acre-foot
acft/yr	acre-foot per year
AE	Irrigation Application Efficiencies
ARM	Absolute Residual Mean
ASTM	American Standard Testing Materials
Avg	Average
BAS	MODFLOW Basic Package
BF	Baseflow
BIGS	Big Springs
Calc	Calculated by Model
CALMIT	Center for Advanced Land Management Information Technologies
cf	cubic feet
cfs	cubic foot per second
CMU	Central Model Unit (Previous COHYST model)
CNPPID	Central Nebraska Public Power and Irrigation District
CO	Colorado
COHYST 2010	Cooperative Hydrology Study, of which this report is a part
CPNRD	Central Platte Natural Resources District
CROPSIM	Crop Simulation Model (Soil Water Balance)
CSD	Conservation Survey Division; also cited as NCSD
DEM	Digital Elevation Model
DIS	MODFLOW Discretization Package
DNR, NDNR, or Department	Nebraska Department of Natural Resources
DOI	U.S. Department of Interior
DP	Deep Percolation
DRN	MODFLOW Drain Package
EMU	Eastern Model Unit (Previous COHYST model)
EOM	End of Month
ET	Evapotranspiration
EVT	MODFLOW Evapotranspiration Package
FERC	Federal Energy Regulatory Commission
ft	feet
ft/d	foot per day

Abbreviation/Acronym	Descriptor
ft/mi	feet per mile
ft-msl	feet above mean sea level
FWS	U.S. Fish and Wildlife Service
GHB	MODFLOW General Head Boundary
GIS	Geographic Information System
GOTH	Gothenburg
GUI	Graphical User Interface
GW	Groundwater
GW I	Groundwater Inflow
GWO	Groundwater Outflow
HDR	HDR Engineering, Inc.
Hist	Historical
HSU	Hydrostratigraphic Units
I	Applied Irrigation Water
IMP	Integrated Management Plan
in.	inch
in/yr	inch per year
K	Hydraulic Conductivity
K _v	Vertical Hydraulic Conductivity
LPF	MODFLOW Layer Property Flow
LWA	Lee Wilson and Associates
M&I	Municipal and Industrial
MF2K	MODFLOW-2000
MGD	million gallons per day
mi	mile
mi ² or sq.mi.	square miles
MODFLOW	Modular three-dimensional finite-difference ground-water flow model
NASS	National Agricultural Statistics Service
NCSD	Nebraska Conservation and Survey Division (we may want to cross-reference with CSD)
NDNR, DNR, or Department	Nebraska Department of Natural Resources
NE	Nebraska
NGPC	Nebraska Game and Parks Commission
NHD	National Hydrographic Dataset
NIR	Net Irrigation Requirement

Abbreviation/Acronym	Descriptor
NPPD	Nebraska Public Power District
NRCS	Natural Resource Conservation Service (Natural Resources Conservation Service)
NRD	Natural Resources District
NWIS	National Water Information System (of the USGS)
P	Precipitation
PEST	Parameter Estimation
PRRIP	Platte River Recovery Implementation Program
QA/QC	Quality Assurance and Quality Control
R	Recharge
RCH	MODFLOW Recharge Package
RGL	Reach Gain/Loss
RIV	MODFLOW River Package
RMSE	Root Mean Square Error
RO	Runoff
sqft/d	foot squared per day
Ss	Specific Storage
STATSGO	State Soil Geographic Database
STELLA	Software programs to facilitate the mapping, modeling, simulation, and communication of dynamic processes
STO	Storage
STR	MODFLOW Stream Package
SW	Surface Water
SWAT	Surface Water Assessment Tool
SWI	Surface Water Inflow
SWO	Surface Water Outflow
Sy	Specific Yield
TBNRD	Tri-Basin Natural Resources District
TPNRD	Twin Platte Natural Resources District
UNL	University of Nebraska at Lincoln
USDA	U.S. Department of Agriculture
USGS	U.S. Geological Survey
WEL	MODFLOW Pumping Package
WHAT	Web-Based Hydrograph Analysis Tool
WL	Water Level

GLOSSARY

Acre-foot (acft, acre-ft, AF) – the volume of water required to cover 1 acre of land (43,560 square feet) to a depth of 1 foot. Equal to 325,851 gallons or 1,233 cubic meters.

Alluvium – deposits of clay, silt, sand, gravel, or other particulate material that has been deposited by a stream or other body of running water in a streambed, on a flood plain, on a delta, or at the base of a mountain.

Aquifer – a geological formation or structure that stores and/or transmits water, such as to wells and springs. Use of the term is usually restricted to those water-bearing formations capable of yielding water in sufficient quantity to constitute a usable supply for people's uses.

Aquifer (confined) – soil or rock below the land surface that is saturated with water. There are layers of impermeable material both above and below it and it is under pressure so that when the aquifer is penetrated by a well, the water will rise above the top of the aquifer.

Aquifer (unconfined) – an aquifer whose upper water surface (water table) is at atmospheric pressure, and thus is able to rise and fall.

Artesian Water – groundwater that is under pressure when tapped by a well and is able to rise above the level at which it is first encountered. It may or may not flow out at ground level. The pressure in such an aquifer commonly is called artesian pressure, and the formation containing artesian water is an artesian aquifer or confined aquifer. See flowing well.

Artificial Recharge – an process where water is put back into groundwater storage from surface water supplies such as irrigation, or induced infiltration from streams or wells.

Baseflow – sustained flow of a stream in the absence of direct runoff. It includes natural and human-induced streamflows. Natural base flow is sustained largely by groundwater discharges.

Bedrock – the solid rock beneath the soil and superficial rock. A general term for solid rock that lies beneath soil, loose sediments, or other unconsolidated material.

Consumptive Use – that part of water withdrawn that is evaporated, transpired by plants, incorporated into products or crops, consumed by humans or livestock, or otherwise removed from the immediate water environment. Also referred to as water consumed.

Conveyance Loss – water that is lost in transit from a pipe, canal, or ditch by leakage or evaporation. Generally, the water is not available for further use; however, leakage from an irrigation ditch, for example, may percolate to a groundwater source and be available for further use.

Cubic Feet Per Second (cfs) – a rate of the flow, in streams and rivers, for example. It is equal to a volume of water one foot high and one foot wide flowing a distance of one foot in one second. One "cfs" is equal to 7.48 gallons of water flowing each second. As an example, if your car's gas tank is 2 feet by 1 foot by 1 foot (2 cubic feet), then gas flowing at a rate of 1 cubic foot/second would fill the tank in two seconds.

Discharge – the volume of water that passes a given location within a given period of time. Usually expressed in cubic feet per second.

Domestic Water Use – water used for household purposes, such as drinking, food preparation, bathing, washing clothes, dishes, pets, flushing toilets, and watering lawns and gardens. About 85% of domestic water is delivered to homes by a public-supply facility, such as a county water department. About 15% of the Nation's population supply their own water, mainly from wells.

Drainage Basin – land area where precipitation runs off into streams, rivers, lakes, and reservoirs to a central point. It is a land feature that can be identified by tracing a line along the highest elevations between two areas on a map, often a ridge. Large drainage basins, like the area that drains into the Mississippi River contain thousands of smaller drainage basins. Also called a “watershed.”

Drawdown – a lowering of the groundwater surface caused by pumping.

Effluent – water that flows from a sewage treatment plant after it has been treated.

Evaporation – the process of liquid water becoming water vapor, including vaporization from water surfaces, land surfaces, and snow fields, but not from leaf surfaces. See transpiration.

Evapotranspiration – the sum of evaporation and transpiration.

Flood – An overflow of water onto lands that are used or usable by man and not normally covered by water. Floods have two essential characteristics: The inundation of land is temporary; and the land is adjacent to and inundated by overflow from a river, stream, lake, or ocean.

Flood Plain – a strip of relatively flat and normally dry land alongside a stream, river, or lake that is covered by water during a flood.

Flowing Well/Spring – a well or spring that taps groundwater under pressure so that water rises without pumping. If the water rises above the surface, it is known as a flowing well.

Freshwater – water that contains less than 1,000 milligrams per liter (mg/L) of dissolved solids; generally, more than 500 mg/L of dissolved solids is undesirable for drinking and many industrial uses.

Gage Height – the height of the water surface above the gage datum (zero point). Gage height is often used interchangeably with the more general term, stage, although gage height is more appropriate when used with a gage reading.

Gaging Station – a site on a stream, lake, reservoir or other body of water where observations and hydrologic data are obtained. The U.S. Geological Survey and other agencies measure stream discharge at gaging stations.

Gallons per Capita per Day – Annual water use by municipal water utility divided by the population and the number of days in a year.

Groundwater – (1) water that flows or seeps downward and saturates soil or rock, supplying springs and wells. The upper surface of the saturated zone is called the water table. (2) Water stored underground in rock crevices and in the pores of geologic materials that make up the Earth's crust.

Groundwater, Confined – groundwater under pressure significantly greater than atmospheric, with its upper limit the bottom of a bed with hydraulic conductivity distinctly lower than that of the material in which the confined water occurs.

Groundwater Recharge – inflow of water to a groundwater reservoir from the surface. Infiltration of precipitation and its movement to the water table is one form of natural recharge. Also, the volume of water added by this process.

Groundwater, Unconfined – water in an aquifer that has a water table that is exposed to the atmosphere.

Headwater(s) – (1) the source and upper reaches of a stream; also the upper reaches of a reservoir. (2) the water upstream from a structure or point on a stream. (3) the small streams that come together to form a river. Also may be thought of as any and all parts of a river basin except the mainstream river and main tributaries.

Hydraulic Conductivity – the ease with which water can move through porous media. Units are expressed as a rate, such as ft/day.

Hydroelectric Power Water Use – the use of water in the generation of electricity at plants where the turbine generators are driven by falling water.

Hydrologic Cycle – the cyclic transfer of water vapor from the Earth's surface via evapotranspiration into the atmosphere, from the atmosphere via precipitation back to earth, by infiltration into soils and aquifers, and through runoff and baseflow into streams, rivers, and lakes, and ultimately into the oceans.

Impermeable Layer – a layer of solid material, such as rock or clay, which does not allow water to pass through.

Industrial Water Use – water used for industrial purposes in such industries as steel, chemical, paper, and petroleum refining. Nationally, water for industrial uses comes mainly (80%) from self-supplied sources, such as a local wells or withdrawal points in a river, but some water comes from public-supplied sources, such as the county/city water department.

Infiltration – flow of water from the land surface into the subsurface.

Irrigation – the controlled application of water for agricultural purposes through manmade systems to supply water requirements not satisfied by rainfall.

Irrigation Water Use – water application on lands to assist in the growing of crops and pastures or to maintain vegetative growth in recreational lands, such as parks and golf courses.

Land Use – Use of land for agricultural, industrial, residential, recreational, or other purposes.

Livestock Water Use – water used for livestock watering, feed lots, dairy operations, fish farming, and other on-farm needs.

Million Gallons Per Day (Mgd) – a rate of flow of water equal to 133,680.56 cubic feet per day, or 1.5472 cubic feet per second, or 3.0689 acre-feet per day. A flow of one million gallons per day for one year equals 1,120 acre-feet (365 million gallons).

Municipal Water System – a water system that has at least five service connections or which regularly serves 25 individuals for 60 days; also called a public water system.

Peak Flow – the maximum instantaneous discharge of a stream or river at a given location. It usually occurs at or near the time of maximum stage.

Percolation – (1) The movement of water through the openings in rock or soil. (2) the entrance of a portion of the streamflow into the channel materials to contribute to groundwater replenishment.

Permeability – the ability of a material to allow the passage of a liquid, such as water through rocks. Permeable materials, such as gravel and sand, allow water to move quickly through them, whereas impermeable material, such as clay, don't allow water to flow freely.

Porosity – a measure of the water-bearing capacity of subsurface rock. With respect to water movement, it is not just the total magnitude of porosity that is important, but the size of the voids and the extent to which they are interconnected, as the pores in a formation may be open, or interconnected, or closed and isolated. For example, clay may have a very high porosity with respect to potential water content, but it constitutes a poor medium as an aquifer because the pores are usually so small. The term Effective Porosity is often used to describe the porosity that is conducive to flow.

Precipitation – water from the atmosphere that reaches the land surface in the form of rain, snow, hail, sleet, dew, or frost.

Public Supply – water withdrawn by public governments and agencies, such as a county water department, and by private companies that is then delivered to users. Public suppliers provide water for domestic, commercial, thermoelectric power, industrial, and public water users. Most people's household water is delivered by a public water supplier. The systems have at least 15 service connections (such as households, businesses, or schools) or regularly serve at least 25 individuals daily for at least 60 days out of the year.

Rating Curve – A drawn curve showing the relation between gage height and discharge of a stream at a given gaging station.

Recharge – water added to an aquifer. For instance, rainfall that seeps into the ground and percolates to the water table.

Reservoir – a pond, lake, or basin, either natural or artificial, for the storage, regulation, and control of water.

Return Flow – (1) That part of a diverted flow that is not consumptively used and returned to its original source or another body of water. (2) (Irrigation) Drainage water from irrigated farmlands that re-enters the water system to be used further downstream. (3) (Wastewater) Water returned to the environment by wastewater-treatment facilities.

River – A natural stream of water of considerable volume, larger than a brook or creek.

Runoff – (1) That part of the precipitation, snowmelt, or irrigation water that appears in uncontrolled surface streams, rivers, drains or sewers. Runoff may be classified according to speed of appearance after rainfall or melting snow as direct runoff or base runoff, and according to source as surface runoff, storm interflow, or groundwater runoff. (2) The total discharge described in (1), above, during a

specified period of time. (3) Also defined as the depth to which a drainage area would be covered if all of the runoff for a given period of time were uniformly distributed over it.

Sedimentary Rock – rock formed of sediment, and specifically: (1) sandstone and shale, formed of fragments of other rock transported from their sources and deposited in water; and (2) rocks formed by or from secretions of organisms, such as most limestone. Many sedimentary rocks show distinct layering, which is the result of different types of sediment being deposited in succession.

Seepage – (1) The slow movement of water through small cracks, pores, interstices, etc., of a material into or out of a body of surface or subsurface water. (2) The loss of water by infiltration into the soil from canals, ditches, laterals, watercourses, reservoirs, storage facilities, other bodies of water, or from fields.

Self-Supplied Water – water withdrawn from a surface water or groundwater source by a user rather than being obtained from a public supply. An example would be homeowners getting their water from their own well.

Specific Yield – quantity of water which a unit volume of aquifer, after being saturated, will yield by gravity. It is expressed as a ratio of groundwater volume to the volume of the aquifer.

Spring – a water body formed when the side of a hill, a valley bottom or other excavation intersects a flowing body of groundwater at or below the local water table, below which the subsurface material is saturated with water.

Storage – a general term for the amount of water in a reservoir or an aquifer.

Stream – a general term for a body of flowing water; natural watercourse containing water at least part of the year. In hydrology, it is generally applied to the water flowing in a natural channel as distinct from a canal.

Streamflow – the water discharge that occurs in a natural channel. A more general term than runoff, streamflow may be applied to discharge whether or not it is affected by diversion or regulation.

Surface Water – water that is on the Earth's surface, such as in a stream, river, lake, or reservoir.

Transmissivity – the capacity of a rock to transmit water under pressure. The coefficient of transmissivity is the rate of flow of water, at the prevailing water temperature, in gallons per day, through a vertical strip of the aquifer one foot wide, extending the full saturated height of the aquifer under a hydraulic gradient of 100-percent. A hydraulic gradient of 100-percent means a one foot drop in head in one foot of flow distance.

Transpiration – process by which water that is absorbed by plants, usually through the roots, is evaporated into the atmosphere from the plant surface, such as leaf pores. See evapotranspiration.

Tributary – a smaller river or stream that flows into a larger river or stream. Usually, a number of smaller tributaries merge to form a river.

Unsaturated Zone – the zone immediately below the land surface where the pores contain both water and air, but are not totally saturated with water. These zones differ from an aquifer, where the pores are saturated with water. Also referred to as the Vadose Zone.

Wastewater – water that has been used in homes, industries, and businesses that is not for reuse unless it is treated.

Water Table – the top of the water surface in the saturated part of an unconfined aquifer.

Water Use – water that is used for a specific purpose, such as for domestic use, irrigation, or industrial processing. Water use pertains to human's interaction with and influence on the hydrologic cycle, and includes elements, such as water withdrawal from surface- and groundwater sources, water delivery to homes and businesses, consumptive use of water, water released from wastewater-treatment plants, water returned to the environment, and instream uses, such as using water to produce hydroelectric power.

Watershed – the land area that drains water to a particular stream, river, or lake. It is a land feature that can be identified by tracing a line along the highest elevations between two areas on a map, often a ridge. Large watersheds, like the Platte River basin contain thousands of smaller watersheds.

Well (Water) – an artificial excavation put down by any method for the purposes of withdrawing water from the underground aquifers. A bored, drilled, or driven shaft, or a dug hole whose depth is greater than the largest surface dimension and whose purpose is to reach underground water supplies or oil, or to store or bury fluids below ground.

Withdrawal – water removed from a ground- or surface-water source for use.